

Multisplit FreeMatch DC Inverter Primary Heating



New 2009

4 power levels: 2,00~5,30 kW.



Floor standing HFIU XR

2 airflow out controls: upper and lower or just lower, for the best comfort in winter.

5 fan speeds.

Frontal and lateral air-intake.

Anti-formaldehyde filter.

IR remote controller.

Model			HFIU 205 XR	HFIU 265 XR	HFIU 355 XR	HFIU 535 XR
Type			DC Inverter	DC Inverter	DC Inverter	DC Inverter
Capacity	Cooling	kW	2,00	2,60	3,20	5,30
	Heating	kW	2,50	3,00	4,00	6,00
Power supply		Ph-V-Hz	1-220~230V-50HZ			
		I.U.-O.U.	O.U.			
Wiring cables i.u./o.u. (without ground)		n°	3 (plug cable 6 mt.)			
Refrigerant Pipe Liquid/Gas side		mm(inch.)	6,35(1/4") - 12,7(1/2")			
Specifications						
Indoor Unit		Dimension (WxHxD)	700x600x210			
		Net	13		15	
Indoor Noise level 1 m (Hi/Mi/Lo)		dB(A)	37/31/22		37/32/23	39/33/28
Indoor Noise level 2,5 m (Hi/Mi/Lo)		dB(A)	29/23/14		29/24/15	31/25/20
Moisture Removal		l/h	1,00		1,20	1,50
Indoor air flow (Hi/Mi/Lo)		m³/h	550/460/330		550/460/350	740/640/440
Drain hose diameter		mm	16			
Remote Controller (st. equipment)		type	IR Wireless			
Options						
Wired control			DTW VEH / DTW IHXR			