

Binder File III

FIRE-RESISTANT DOCUMENT PROTECTION

Key Features

- Approved for two hours' fire protection of documents in fire class 120 Paper in accordance with NT Fire 017.
- Maximised capacity extra-wide cabinet for the storage of ring binders (22 per drawer based on a 60mm-wide binder).
- The 31" cabinet is available with 2, 3 or 4 drawers.
- Low-weight cabinets for reduced transportation and installation costs, and lighter floor loads.
- Insulation between drawers means each drawer's contents are protected in a fire even if one drawer is left open.
- All models fitted with day-catch locking for extra protection.

- For easier access, high-strength slides allow drawers to be pulled out 110%.
- Interlocking system prevents more than one drawer being open at once and eliminates risk of tipping.
- Entire inner body lined with steel for protection from insulation dust.
- All cabinets fitted with high-quality key lock as central lock.
- Light grey, powder-coated finish and smooth-edge design.
- Binder File III is manufactured in accordance with ISO 9001 for quality management systems and ISO 14001 for environmental management systems.













Product Specifications

	External (mm)			Internal (mm)*				
Model	Height	Width	Depth	Height	Width	Depth	Weight (kg)	Capacity (binders)
2 Drw	826	729	771	325	637	660	239	44
3 Drw	1208	729	771	325	637	660	328	66
4 Drw	1590	729	771	325	637	660	416	88

^{*}Internal dimensions per drawer

Capacity Comparison

Considering its low weight and relatively small footprint, Binder File III offers considerable storage capacity for ring binders.

The following table shows how many metres of shelving are required to store the same amount of binders as a Binder File III cabinet.

Model	No. of binders*	Equivalent metres of shelving required		
2 Drw	44	2.64m		
3 Drw	66	3.96m		
4 Drw	88	5.28m		

^{*}Based on binders with a 60mm-wide spine.

Lock Options

Binder File III filing cabinets are fitted with a central, highquality key lock which locks all drawers simultaneously.

Every model also has day-catch locking so that even when unlocked centrally, a drawer need only be pushed shut to guarantee the full protection of its contents.

Fire Testing

Binder File III has been approved in accordance with the Scandinavian standard, NT Fire 017, in fire class 120 Paper¹. This means the filing cabinet will protect paper documents for two hours.

Test Procedure



Stage 1
The cabinet is placed in a furnace and heated to a temperature of over 1000 °C for 120 minutes to simulate the effects of a severe fire.



Stage 2
The cabinet is removed from the furnace and cooled. When opened, the inner temperature of the cabinet must not exceed 150 °C.

¹Certification awarded by SP (Swedish National Testing and Research Institute).

Authorised dealer:

