

Innovative safe for
certified Grade II
burglary protection



ProGuard

BURGLARY-RESISTANT PROTECTION

Key Features

- Burglary protection in accordance with the European standard, EN 1143-1, as certified by ECB+S for Grade II.
- ProGuard's new composite, torch-resistant barrier material ensures burglary protection whilst also reducing its total weight. Less weight helps keep transportation and installation costs at a minimum.
- The three-way boltwork is constructed with solid steel bolts.
- For additional security, ProGuard is fitted with an active relocker and anti-drilling plates have been incorporated into the boltwork to withstand burglary attempts.
- A Class A mechanical key lock or a Class B high-security electronic lock, approved in accordance with EN 1300, are both available as primary lock options. Electronic locks increase the level of security and prevent unauthorised access to the safe.
- Every model can be customised with a range of internal fittings to maximise storage capacity.
- ProGuard has a modern design with an ergonomic soft-touch handle.



Chubbsafes
Trusted the world over.

BURGLARY
PROTECTION

Product Specifications

Model	External (mm)			Internal (mm)			Weight (kg)	Volume (litres)
	Height	Width	Depth	Height	Width	Depth		
60	530	500	521	430	400	360	250	62
110	690	600	561	590	500	386	334	114
150	875	600	561	775	500	386	402	150
200	1150	600	561	1050	500	386	501	203
300	1600	600	561	1500	500	386	655	290
350	1600	675	585	1500	575	410	731	354

Lock Options



Electronic Lock

As the primary locking option, ProGuard safes can be fitted with either a high-security electronic lock (Class B) or a key lock (Class A).

Dual locking is available from model 110. The primary lock can be complemented by a combination lock or both a key lock and electronic lock can be fitted.

All locks are tested by ECB•S and are certified in accordance with the EN 1300 standard.

ProGuard's high-security electronic lock – certified Class B by ECB•S – includes the following features:

- 1 master code, 1 supervisor code and 7 user codes.
- Time delay of up to 99 minutes between lock being operated and door being opened. Also equipped with time-delay override.
- Protective function to raise silent alarm if lock is being opened under duress.

Burglary Testing

ProGuard has been approved by ECB•S in accordance with the European standard, EN 1143-1, for burglary protection in Grade II.


A range of attack tools were used to test ProGuard's level of resistance, from basic tools to sophisticated thermal and electrical equipment.




Internal Fittings



Shelf



Extendable shelf




Extendable drawer




Lockable compartment



Suspension file frame



Extendable tray



Shelf for hanging files
(available for size 110 and above)

Authorised dealer

Chubbsafes
Trusted the world over.

www.chubbsafes.com

'Chubb' is owned by Chubb plc and is a registered trademark used under license