

The File III 120

FIRE-RESISTANT DOCUMENT PROTECTION



- Approved for two hours' fire protection of documents in fire class 120 Paper in accordance with NT Fire 017.
- Maximised storage capacity the 31" cabinet is available with 2, 3 or 4 drawers.
- Low-weight cabinets for reduced transportation and installation costs, and lighter floor loads.
- All models are available in both A4 and Folio format.
- Insulation between drawers means each drawer's contents are protected in a fire even if one drawer is left open.
- All models fitted with day-catch locking for extra protection.
- For easier access, high-strength slides allow drawers to be pulled out 110%.

- Interlocking system prevents more than one drawer being open at once and eliminates risk of tipping.
- Entire inner body lined with steel for protection from insulation dust.
- All cabinets fitted with high-quality key lock as standard.
- Light grey, powder-coated finish and smooth-edge design.
- The File III 120 is manufactured in accordance with ISO 9001 for quality management systems and ISO 14001 for environmental management systems.













Product Specifications

	External (mm)			Internal (mm)*				
Model	Height	Width	Depth	Height	Width	Depth	Weight (kg)	Capacity (mm)
31" – 2 Drawer (A4)	736	465	771	288	330	660	153	1320
31" – 3 Drawer (A4)	1073	465	771	288	330	660	209	1980
31" – 4 Drawer (A4)	1410	465	771	288	330	660	265	2640
31" – 2 Drawer (Folio)	736	525	771	288	330	660	167	1320
31" – 3 Drawer (Folio)	1073	525	771	288	330	660	227	1980
31" – 4 Drawer (Folio)	1410	525	771	288	330	660	287	2640


^{*} Internal dimensions per drawer

Lock Options

The File III 120 filing cabinets are fitted with a single highquality key lock as standard. As an option, a combination lock may also be added for dual central locking. In addition, each individual drawer may be fitted with its own key lock. An electronic lock is available on request.

Every model also has day-catch locking so that even when unlocked centrally, a drawer need only be pushed shut to guarantee the full protection of its contents.


Internal Fittings





Bottom plate

Data media insert



Tilt support for bottom plate

Fire Testing

The File III 120 has been approved in accordance with the established European standard, NT Fire 017, in fire class 120 Paper, which means the filing cabinet will protect paper documents for two hours. The certification was awarded by SP (Swedish National Testing and Research Institute).

Test Procedure



Stage 1
The cabinet is placed in a furnace and heated to a temperature of over 1000 °C for 120 minutes to simulate the effects of a severe fire.



Stage 2
The cabinet is removed from the furnace and cooled. When opened, the inner temperature of the cabinet must not exceed 150 °C.

