


## ILC 150 ETH

Order No.: 2985330

<http://eshop.phoenixcontact.net/phoenix/treeViewClick.do?UID=2985330>

Inline Controller with Ethernet interface for coupling to other controllers and systems, with programming options according to IEC 61131-3, complete with connector and labeling field.

Commercial data	
EAN	 4 046356 096409
Pack	1 pcs.
Customs tariff	85371091
Product key	11221
country of origin	DE
Catalog page information	Page 19 (AX-2011)

### Product notes

WEEE/RoHS-compliant since:  
02/21/2007



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Product description

With the ILC 150 ETH, the highly modular Inline Controller range from Phoenix Contact has been extended to include a high-performance compact controller. This controller can be used to extend the possible field of application of Inline Controllers right down to smaller applications. With direct integration in the Inline automation system, the compact controller is highly modular and can be adapted to the relevant application requirements. Its integrated Ethernet interface enables parameterization and programming using PC WorX automation software according to IEC 61131, and it can also exchange data with OPC servers simultaneously and communicate with TCP/IP-compatible devices.

The Inline Controller range covers a wide performance range. From entry-level versions through to high-end controllers, users can find the right controller for their application. Within the product portfolio, users can choose between controllers with different computing capacities, with or without PROFINET IO controllers, and with or without GL approval.

## Technical data

### Control system

Programming tool	PC WORX 5
Diagnostics tool	DIAG+ from version 1.14

### Mechanical design

Height	119.8 mm
Width	80 mm
Depth	71.5 mm
Weight	285 g
Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	10 % ... 95 % (according to DIN EN 61131-2)
Permissible humidity (storage/transport)	10 % ... 95 % (according to DIN EN 61131-2)
Air pressure (operation)	70 kPa ... 106 kPa (up to 3000 m above mean sea level)
Air pressure (storage/transport)	70 kPa ... 106 kPa (up to 3000 m above mean sea level)
Vibration (operation)	5 g

### Data interfaces

Interface	INTERBUS local bus (master)
Connection method	Inline data jumper
Interface	Parameterization/operation/diagnostics
Connection method	RS-232-C, 6-pos. MINI-DIN female connector (PS/2), Ethernet 10/100 (RJ45)
Interface	Ethernet 10Base-T/100Base-TX
Connection method	RJ45 female connector
Transmission speed	10/100 MBit/s

### Power supply

Typical current consumption	210 mA
Max. current consumption	870 mA (370 mA communications power + 500 mA analog voltage supply)
Supply voltage	24 V DC
Supply voltage range	19.2 V DC ... 30 V DC

Residual ripple	± 5 %
-----------------	-------

**INTERBUS data**

Type	INTERBUS master
Number of Inline terminals which can be connected	63
Note on the number of Inline terminals which can be connected	observe current consumption
Number of devices with parameter channel (PCP)	max. 16
Number of supported devices	max. 128
Number of I/O nodes	max. 4096
Battery	Integrated (rechargeable battery buffered)
Number of control tasks	8
Number of timers, counters	(Depends on data memory)
Number of data blocks	(Depends on data memory)
Data memory	256 kByte
Retentive data memory	8 kByte (NVRAM)

**IEC 61131 runtime system**

Programming tool	PC WORX 5
Processing speed	1.5 ms (1 K mix instructions) 90 µs (1 K bit instructions)
Data memory	256 kByte
Retentive data memory	8 kByte (NVRAM)
Number of data blocks	(Depends on data memory)
Number of timers, counters	(Depends on data memory)
Number of control tasks	8
Realtime clock	Yes

**Inline potential routing**

Communications power $U_L$	7.5 V DC ±5%
Power supply at $U_L$	max. 0.8 A DC (observe derating)
Main circuit supply $U_M$	24 V DC -15% / +20% (in acc. with EN 61131-2)
Power supply at $U_M$	max. 8 A DC (Sum of $U_M + U_S$ )
Current consumption from $U_M$	max. 8 A DC
Segment supply voltage $U_S$	24 V DC -15% / +20% (in acc. with EN 61131-2)
Power supply at $U_S$	max. 8 A (Sum of $U_M + U_S$ )

Current consumption from $U_s$	max. 8 A DC
I/O supply voltage $U_{ANA}$	24 V DC -15% / +20%
Power supply at $U_{ANA}$	0.5 A DC (observe derating)

### Certificates / Approvals



Certification	ABS, BV, CUL, DNV, GL, LR, UL
Certification Ex:	PxC-EX

### Accessories

Item	Designation	Description
<b>Cable/conductor</b>		
2730611	PRG CAB MINI DIN	Connection cable, to connect Remote Field Controllers to a PC (RS-232) for PC WORX, 3 m in length
<b>Memory</b>		
2988120	SD FLASH 256MB	Program and configuration memory, plug-in, 256 MB
2988816	SD FLASH 256MB APPLIC A	Program and configuration memory, plug-in, 256 MB with license key for function block libraries, e.g., for SNMP, SQL, wireless, motion functions, etc.
2700551	SD FLASH 256MB PDPI BASIC	Program and configuration memory, plug-in, 256 MB with license key for licensing PDPI controller blocks.
2700552	SD FLASH 256MB PDPI PRO	Program and configuration memory, plug-in, 256 MB with license key for licensing PDPI controller blocks.
<b>Software</b>		
2985945	AX OPC SERVER	AX OPC SERVER, communication interface for OPC-capable visualization with PC WORX-based controls.

ILC 150 ETH Order No.: 2985330

<http://eshop.phoenixcontact.net/phoenix/treeViewClick.do?UID=2985330>

---

**Address**

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 00  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



© 2011 Phoenix Contact  
Technical modifications reserved;