TPWLKI SERIES STAINLESS STEEL PALLET TRUCK SCALE



OPTIONS ONLY AVAILABLE AT TIME OF ORDER

- Thermal printer / Modem radio option box
- WI-FI interface
- Alibi memory with time-date
- Time-Date
- Versions with special capacities and/or divisions or high resolution (ask for price estimate)

KEYBOARD FUNCTIONS AND PRINTOUT

- KEYBOARD: Zeroing, automatic tare, print and/or data transmission command, activation of selected function, presettable tare, ID1 code, ID2 code, 10 recallable tare values.
- **PRINTOUT:** configurable layout with: 4 header rows, net weight, gross weight, tare weight or weight totalized and total weigh, time/date, ticket number, weigh number.

Stainless steel pallet truck scales with built-in multirange electronic weighing, easy to use. Weight detection with four IP68 stainless steel load cell. Sturdy structure suitable for harsh work conditions. Available also CE-M APPROVED.

MAIN FEATURES

- Maximum lifting capacity: 2000 kg.
- Accuracy +/- 0.1% of the maximum capacity.
- Fork dimensions 1180 x 550 x 80 mm. Weighs about 135 kg.
- Bearing structure entirely in extra thick STAINLESS steel.
- Lifting pump in STAINLESS steel.
- Steering wheels and double loading rollers in nylon.
- 4 IP68 stainless steel shear beam load cells.
- IP65 stainless steel weight indicator, easy to clean and resistant to harsh and corrosive environments; large 25mm backlit LCD display, clearly visible also in poor lighting conditions, and waterproof keypad, with 17 numerical/functional keys.
- Calibration and Set-Up from keyboard or from PC.
- Power supply through built-in rechargeable battery.
- 80-hour approximate operating time or one month with the typical non continuous use, thanks to its auto switch-off function.
- Programmable auto power saving function.
- Low battery warning.
- Equipped with 230Vac 50 Hz battery charger (recharging time is about 8 hours).
- Bi-directional RS232/C port for connection to printer.
- Bi-directional RS232/C port for PC, radio modem, or portable terminal.
- IR input for managing the remote control

SELECTABLE FUNCTIONS

- High Resolution Weighing x 10
- Net/Gross or Ib/kg conversion
- Accumulation
- Formula weighing
- +/- Checkweighing
- Percentage weighing
- Counting (Max. resolution of 1.500.000 divisions)
- In/Out weighing

Versions available				
Code	Max Capacity kg	Division kg	CE-M Division kg	HR Division kg
TPWLKI	500 / 1000 / 2000	0,2 / 0,5 / 1	-	0,1
TPWLKIM M	1000 / 2000	-	0,5 / 1	-

Options only available at time of order			
Code	Description		
EHR	High resolution model for internal factory use.		
TPRXTP	Thermal printer for mounting on the pallet truck column, with stainless steel case and ABS door for protection from		
	sprays and dust. IP65 protection.		
DFCLK	Real Time Clock (Time/date)		
ALMEM	Alibi memory (fiscal memory) with time/date; max. 120.000 weighs		

WIFIT WI-FI interface for wireless connection (through access point) to the company computer system.