



FPD/LSI Inspection Microscopes

ECLIPSE L300N/L300ND L200N/L200ND

FPD/LSI Inspection Microscopes





L300N

For ø300 mm wafer/
Episcopic illumination type



L300ND

For 17-inch FPD/
Episcopic and Diascopic illumination type



L200N

For ø200 mm wafer/
Episcopic illumination type



L200ND


For ø200 mm wafer/
Episcopic and Diascopic illumination type

Enhanced observation performance and operation


Epi-fluorescence observation widens inspection range—including 365 nm UV excitation

- Highly beneficial when inspecting semiconductor resist residues and organic electroluminescence displays.
- Various observation methods such as brightfield, darkfield, simple polarizing, and DIC are possible on all models.
- With the L300ND/L200ND, diascopic illumination capability adds the illumination through transparent substrates.


*L300N/L300ND/L200ND only




Brightfield observation
of wafer pattern



Darkfield observation



DIC observation



Epi-fluorescence observation of
organic substance on wafer


Front operation with easy access

- Minimizes fatigue during lengthy observations




Target for easier focusing

- Insert a focusing target in the optical path to easily focus on low-contrast samples, such as bare wafers.



Stronger safeguard against contamination

- Antistatic coatings applied to the body, stage, eyepiece tube and other various controls
- Prevents damage to samples and contributes to higher yields



Observation at optimum eyepoint level

- Ultra-wide 25-mm field of view and eyepiece angle adjustment between 0 ° and 30 °
- Operators can adjust eyepoint level to ensure a comfortable viewing position

Illumination

LED


Compact LED illuminators are power saving and achieve long life.



LV-LL LED Lamphouse

Intensilight

- Motorized mercury precentered fiber illuminator for epi-fluorescence observation, with variable light intensity and shutter control, provide excellent flexibility. Lamp centering and focus adjustment are not necessary.



*L300N/L300ND/L200ND only

Fixed-position X-Y fine movement control

- Allows for stage movements and focusing to be carried out with ease



Filter blocks

For epi-fluorescence observation

- EPI-FL UV-2A
- EPI-FL B-2A
- EPI-FL V-2A
- EPI-FL G-2A
- EPI-FL BV-2A



*L300N/L300ND/L200ND only. Only one cube is attachable.

Accessories

Objective lenses

Standard objective lenses

TU Plan Fluor Series

EPI/BD 5x/10x/20x/50x/100x

Enable brightfield, darkfield, simple polarizing, sensitive polarizing, differential interference, and epi-fluorescence observations with just one lens. Achieves superior chromatic aberration performance with long working distance for all magnifications to adapt to any application.



*Brightfield observation (EPI) objective lens

Model	Magnification	NA	Working Distance(mm)
TU Plan Fluor EPI (brightfield type)	5x	0.15	23.5
	10x	0.30	17.5
	20x	0.45	4.5
	50x	0.80	1.0
	100x	0.90	1.0
TU Plan Fluor BD (brightfield/ darkfield type)	5x	0.15	18.0
	10x	0.30	15.0
	20x	0.45	4.5
	50x	0.80	1.0
	100x	0.90	1.0

Long working distance objective lenses

TU Plan ELWD Series

EPI/BD 20x/50x/100x

With the phase Fresnel lenses, these objective lenses enable long working distances while offering higher level chromatic aberration correction than conventional objective lenses. This improves operability for samples with different heights.



*Brightfield observation (EPI) objective lens

Model	Magnification	NA	Working Distance(mm)
TU Plan EPI ELWD (brightfield type)	20x	0.4	19.0
	50x	0.6	11.0
	100x	0.8	4.5
TU Plan BD ELWD (brightfield/ darkfield type)	20x	0.4	19.0
	50x	0.6	11.0
	100x	0.8	4.5



Low-magnification objective lenses

T Plan EPI

EPI 1x/2.5x



Model	Magnification	NA	Working Distance (mm)
T Plan EPI (brightfield type)	1x	0.03	3.8
	2.5x	0.075	6.5

Apochromatic objective lenses

TU Plan Apo Series

EPI/BD 50x/100x/150x



By using phase Fresnel lenses, these objective lenses achieve significantly longer operating distances while maintaining the superior chromatic aberration performance of apochromatic lenses.



*Brightfield observation (EPI) objective lens

Model	Magnification	NA	Working Distance (mm)
TU Plan Apo EPI (brightfield type)	50x	0.8	2.0
	100x	0.9	2.0
	150x	0.9	1.5
TU Plan Apo BD (brightfield/ darkfield type)	50x	0.8	2.0
	100x	0.9	2.0
	150x	0.9	1.5

Lenses with correction mechanism

CFI L Plan EPI CR Series

EPI 20x/50x/100x



Model	Magnification	NA	Working Distance (mm)	Glass Thickness Correction Range (mm)
CFI L Plan EPI CR	20x	0.45	10.9-10.0	0-1.2
CFI L Plan EPI CR	50x	0.7	3.9-3.0	0-1.2
CFI L Plan EPI CRA	100x	0.85	1.2-0.85	0-0.7
CFI L Plan EPI CRB	100x	0.85	1.3-0.95	0.6-1.3

Digital cameras

Microscope camera

DS-Fi3

Three main features of the previous models, high-resolution, high sensitivity and low noise, and high-speed live display are offered in 1 camera.



5.9 megapixel Color High-resolution

DS-Ri2

Capable of expressing images as is, this microscope digital camera offers high resolution, color reproduction, and frame rate.

16.25 megapixel Color High-resolution



Frame Rate

30fps (1440×1024)

45fps (1636×1088)

Max Recordable Pixels

2880×2048


4908×3264

Imaging software NIS-Elements

Using a tablet PC

L

Simply installing NIS-Elements L on a tablet PC enables setting and control of DS-Fi3/ DS-Ri2 microscope cameras, live image display, and image acquisition.



Using a desktop PC




A wide variety of tools

NIS-Elements L enables the conducting of simple measurements on images, with input of lines and comments. These can also be written onto and saved with the image, and measurement data can be output.

Measurement function

- Line distance
- Area
- Circle
- Circle distance
- Pitch distance
- Angle




Annotate function

- Line
- Arrow
- Text
- Marker
- Polyline




Image Stitching

Stitches together images acquired from multiple fields of view to create one image.



EDF (Extended Depth of Focus)

Create a single, all-in-focus image from images of differing focus.



Scene Mode

Ten camera setting patterns for optimal color reproduction and contrast for each microscope light source, observation method and type of sample, as well as custom settings, can be selected.

- Wafer/IC
- Metal, Ceramic/Plastic
- Circuit board
- Flat Panel Display

* See the "Digital Camera Digital Sight Series for Microscopes" catalog for details on Digital Sight features.

Wafer loader NWL200

Combined with the NWL200 wafer loader, the ECLIPSE L200N meets requirements for wafer inspections.

Support for ultra-thin 100 µm wafers


- NWL200 series provides levels of safety and reliability that meet all requirements for inspection of the latest wafers.



Improved operability and high throughput


- Setting conditions, such as sampling and inspection patterns, and checking the operating status and content of errors can easily be done with the large LCD panel
- Comprehensive file management functions for carriers and samples are useful for automating inspections
- Exceptionally fast elevator, and the loading and unloading of wafers with complete precision by the multi-arm system all contribute to an efficient wafer transfer and exchange

Dimensional diagram (Unit: mm)




System diagram

ECLIPSE L300N/L300ND



ECLIPSE L200N/L200ND



*1 Discoscopic illumination available only for L300ND and L200ND

*2 Epi-fluorescence observation available only for L300ND/L300N/L200ND

Specifications

	ECLIPSE L300N	ECLIPSE L200N	ECLIPSE L300ND	ECLIPSE L200ND					
Illumination type	Episcopic			Episcopic/Diascopic					
Main body	Power sources for motorized control built in Motorized control for nosepiece, Light intensity control, Aperture diaphragm control								
Nosepiece	Motorized universal sextuple nosepiece								
	Centering Function	Yes	—	Yes					
Focusing mechanism	EPI/DIA changeover	—	—	Yes					
	Cross travel	29 mm							
	Coarse	12.7 mm per rotation (torque adjustable, refocusing mechanism provided)							
Episcopic illuminator	Fine	0.1 mm per rotation (in 1 µm increments)							
	12V-50W halogen lamp light source built in, LV-LL LED Lamphouse Motorized aperture diaphragm (centerable), Fixed field diaphragm (with focus target) Pinhole slider (optional), Four ø25 mm filters (NCB11, ND16, ND4), Polarizer and Analyzer can be mounted Observation methods: Brightfield, Darkfield, Simple polarizing, DIC, Epi-fluorescence*								
	(*L300N/L300ND/L200ND only)								
Diascopic illuminator	—			12V-50W halogen lamp light source built in, LV-LL LED Lamphouse Aperture diaphragm built in LWD condenser built in					
Interface	USB x 1, RS232C (for Intensilight) x 1								
Eyepiece tubes	L2-TT2A Ultra-widefield erect-image tilting trinocular eyepiece tube (tilt angle: 0-30 °) FOV: 22/25; Beam split ratio 100:0/20:80								
	L2-TTA Ultra-widefield erect-image tilting trinocular eyepiece tube (tilt angle: 0-30 °) FOV: 22/25; Beam split ratio 100:0/0:100								
LV-TI3 Trinocular eyepiece tube (erect image) FOV: 22/25; Beam split ratio 100:0/0:100									
Eyepieces	CFI eyepiece lens series								
Objective lenses	CFI60-2/CFI60 system								
Stages	14 x 12 stage	L2-S8A 8 x 8 stage	14 x 12 stage	L2-S8A 8 x 8 stage					
	Stroke	354 x 302 mm	205 x 205 mm	354 x 302 mm					
	Diascopic observation range	354 x 268 mm	150 x 150 mm	354 x 268 mm					
150 x 150 mm									
Coarse/Fine-movement changeover possible Fixed-position X-Y fine-movement controls									
Antistatic mechanism	1000-10 V, within 0.2 sec								
Power consumption	1.2 A/90 W								
Weight (approx.)	Body only	40 kg	30 kg	40 kg					
	With L2-S8A 8 x 8 stage and L2-TTA eyepiece tube	45 kg	45 kg	45 kg					
45 k									

Specifications and equipment are subject to change without any notice or obligation on the part of the manufacturer. July 2019 ©2010-2019 NIKON CORPORATION

N.B. Export of the products* in this brochure is controlled under the Japanese Foreign Exchange and Foreign Trade Law. Appropriate export procedures shall be required in case of export from Japan.
*Products: Hardware and its technical information (including software)



TO ENSURE CORRECT USAGE, READ THE CORRESPONDING MANUALS CAREFULLY BEFORE USING THE EQUIPMENT.



NIKON CORPORATION

Shinagawa Intercity Tower C, 2-15-3, Konan, Minato-ku, Tokyo 108-6290, Japan
phone: +81-3-6433-3701 fax: +81-3-6433-3784
<https://www.nikon.com/products/industrial-metrology/>

ISO 14001 Certified
for NIKON CORPORATION

ISO 9001 Certified
for NIKON CORPORATION
Industrial Metrology Business Unit

NIKON METROLOGY EUROPE NV

Geldenaaksebaan 329, 3001 Leuven, Belgium
phone: +32-16-74-01-00 fax: +32-16-74-01-03

E-mail: Sales.Europe.NM@nikon.com
<http://www.nikonmetrology.com/en-gb>

NIKON METROLOGY UK LTD.

UNITED KINGDOM phone: +44-1332-811-349 fax: +44-1332-639-881
E-mail: Sales.UK.NM@nikon.com

NIKON METROLOGY SARL

FRANCE phone: +33-1-60-86-09-76 fax: +33-1-60-86-57-35
E-mail: Sales.France.NM@nikon.com

NIKON METROLOGY GMBH

GERMANY phone: +49-6023-91733-0 fax: +49-6023-91733-229
E-mail: Sales.Germany.NM@nikon.com

NIKON INSTRUMENTS S.p.A.

ITALY phone: +39-055-300-96-01 fax: +39-055-30-09-93

NIKON METROLOGY, INC.

12701 Grand River Avenue, Brighton, MI 48116 U.S.A.
phone: +1-810-220-4360 fax: +1-810-220-4300

E-mail: Sales.NM-US@nikon.com
<http://www.nikonmetrology.com/en-us>

NIKON CANADA INC.

CANADA phone: +1-905-602-9676 fax: +1-905-602-9953

NIKON MEXICO- Metrology Showroom

MEXICO phone: +52 (442) 688 5067

E-mail: Sales.NM-MX@nikon.com

NIKON INSTRUMENTS (SHANGHAI) CO., LTD.

CHINA (Shanghai branch) phone: +86-21-6841-2050 fax: +86-21-6841-2060
(Beijing branch) phone: +86-10-5831-2028 fax: +86-10-5831-2026

(Guangzhou branch) phone: +86-20-3882-0551 fax: +86-20-3882-0580

NIKON INSTRUMENTS KOREA CO., LTD.

KOREA phone: +82-2-2186-8400 fax: +82-2-555-4415

NIKON SINGAPORE PTE LTD.

SINGAPORE phone: +65-6559-3651 fax: +65-6559-3668

E-mail: NSG.Industrial-sales@nikon.com

NIKON MALAYSIA SDN BHD

MALAYSIA phone: +60-3-7809-3688 fax: +60-3-7809-3633

PT. NIKON INDONESIA

INDONESIA phone: +62-267-864-3949 fax: +62-267-864-3950

E-mail: PTN.Instruments@nikon.com

Nikon Sales (Thailand) Co., Ltd.

THAILAND phone: +66-2633-5100 fax: 66-2633-5191

NIKON INDIA PRIVATE LIMITED

INDIA phone: +91-124-4688500 fax: +91-124-4688527